

## **NSCPT**

### **Nickel Screening Compound Plus - Thinners**

NSCPT is a high purity solvent blend designed for use with Electrolube NSCP, an efficient EMI/RFI screening coating.

The primary use of NSCPT is to dilute and maintain the viscosity of coatings for use in dip and spray coating applications.

<b>Approvals</b>	<b>RoHS-2 Compliant (2011/65/EU):</b>	<b>Yes</b>
Liquid Properties	Appearance	Colourless
	Flash Point (°C)	27
	Density (g/ml @ 20°C)	0.87
	VOC Content (%)	100

<b><u>Description</u></b>	<b><u>Packing</u></b>	<b><u>Order Code</u></b>	<b><u>Shelf Life</u></b>
<u>NSCP Thinners</u>	5 Litre Bulk	NSCPT05L	36 Months

#### **Directions for Use**

**Spray Gun:** For in-house spraying, NSCP can be supplied in bulk containers. The recommended dilution ratio is 1:1 with NSCPT. The thinned solution should be stirred thoroughly and allowed to stand. All air bubbles must be allowed time to disperse before attempting to spray. Thinners should be added gradually until the desired spray pattern and coating weight is achieved. This product is for professional use only.

**Other:** NSCPT thinners may also be used to clean metal equipment found in the application process to include spray guns and other equipment involved.

**Health & Safety:** Always refer to the Health & Safety data sheet before use. These can be downloaded from [www.electrolube.com](http://www.electrolube.com)

Revision 1: Jan 2014